


REV	DESCRIPTION	DATE	BY
A	NEW DRAWING	07/30/15	M.F.

SKT4180


Note: Non-Magnetic



Pointing Accuracy: ± 0.05 mm

Spring Force [$\pm 20\%$]
 13.5g (0.476oz) at initial travel
 32.0g (1.129oz) at 0.60mm (0.0236") recommended travel
 44.3g (1.564oz) at 1.00mm (0.0394") full travel

Material & Finish
 Plunger (Device side) Hardened Beryllium Copper / Non Plated
 Plunger (Board side) Hardened Beryllium Copper / Non Plated
 Barrel Phosphor Bronze / Non Plated
 Spring Hardened Beryllium Copper Wire / Non Plated

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED			
		EMULATION TECHNOLOGY, INC.	
		VLSI and SMT ADAPTERS and ACCESSORIES	
759 FLYNN ROAD		TEL: (805) 383-8480	
CAMARILLO, CA 93012		FAX: (805) 383-8484	
SHEET: 1 OF 1	DATE: 07/30/15	REVISION: A	ASSEMBLY DRAWING
CHECKED:	PREPARED BY: M. FAJARDO	ITEM: POGO-PIN-5.92-1	
DO NOT SCALE DRAWING			DESCRIPTION: POGO-PIN-5.92-1(Non -Magnetic)

Unit : Millimeter[inch]